

## NOTES:

- 1. SUCCESSIVE TAPS INTO THE WATER MAIN SHALL BE A MINIMUM OF 18" ON CENTER.
- 2. ALL SERVICES REQUIRE 36" MINIMUM COVER AT ALL POINTS ALONG SERVICE.
- 3. 1"Ø SERVICES REQUIRE A 2" MINIMUM I.D. CASING PIPE. CASING PIPE SHALL BE SCHEDULE 40 PVC.
- 4. TRACE WIRE TO BE INSTALLED AS PER THIS DETAIL.
- 5. SERVICE SADDLE SHALL BE PER QUALIFIED PRODUCTS LIST.
- 6. 1" POLYETHYLENE TUBING SHALL BE PER QUALIFIED PRODUCTS LIST.
- 7. METERS SHALL BE LOCATED IMMEDIATELY OUTSIDE THE PROPERTY LINE IN THE RIGHT-OF-WAY UNLESS OTHERWISE DIRECTED BY SLWSD (SEE DETAIL SLW-01B).



MINIMUM CONSTRUCTION STANDARDS FOR ST. LUCIE WEST SERVICES DISTRICT 450 SW UTILITY DRIVE, PORT SAINT LUCIE, FL 34986 PHONE: (772) 340-0220

RESIDENTIAL WATER SERVICE CONNECTION

DETAIL: SLW-01A DATE: 03/2020 SCALE: N.T.S.

SHEET: 1 OF 2